



# MORPHOACCESS® J SERIES

### FINGERPRINT ACCESS CONTROL TERMINALS

## ELEGANT DESIGN AND HIGH SECURITY IN A SMALL PACKAGE



#### **Technical characteristics**

**Processor** 

2 ARM9

**Biometric Sensor** 

Optical Sensor: 14x22 mm, 500 dpi, 256 grey levels

Contactless Card Reader (J-Dual)

MIFARE® (1K, 4K) and DESFire® (2K, 4K, 8K)

500 users (\*2 templates) or 3,000 users (\*2 templates)

**Biometric Performances** 

0.6s in 1:1 authentication (J-Dual); 0.8s in 1:500

identification

FAR adjustable from 10<sup>-2</sup> down to 10<sup>-8</sup>

MMI: Multi-color LED, Multi-tone Buzzer

**Operating Modes** 

Standalone, Proxy or Networked

Customizable Wiegand, Clock & Data, RS485, Relay, Ethernet 10/100 Base T, Wi-Fi in option

Security

SSL on TCP/IP network, WEP and WPA encryptions Secure screws, anti-tamper & anti-pulling switches

**Power Supply** 

External 9V to 16V (250mA typical @12V) or Power

**Over Ethernet** 

**Physical Characteristics** 

WxHxD = 80x127x61.5mm (3.15"x5.0"x2.4")

Weight = 193g

**Operating Conditions** 

Temperature: -10°C to +50°C (14°F to 122°F)

Humidity: 10% to 80%

IP 65 (once wall-mounted)

Certifications

CE, CB, FCC, RoHS, REACh

**PC Software Applications** 

MorphoAccess® Enrollment & Management System

Morpho Integrator's Kit (MIK)

The MorphoAccess® J Series fingerprint identification terminals are easy-to-implement access control devices. Combining stylish design and reliability, they bring the security of biometrics to any kind of installation, in prestige premises (corporate offices, buildings etc...) or outdoor environments.

#### Numerous features in a compact design

MorphoTrak

- Stylish, compact and ergonomic design with high quality finishing
- Easy installation: adapted to standard electric boxes, POE powered and configurable by USB flash drive
- Multiple interfaces: compatible with most current or legacy access control systems for standalone or networked operating modes
- Powerful capabilities: Morpho's state-of-the-art optical sensor and biometric algorithms
- Unrivalled levels of security: configurable (down to 10<sup>-8</sup>) and steady FAR, secure DESFire® technology, SSL on TCP/IP, WEP & WPA, anti-tamper hardware
- Robustness: suitable for outdoor environment (IP 65 rated)

#### Two models



#### MorphoAccess<sup>®</sup> J-Bio

to be used for one-to-many fingerprint identification with a database of 500 users (2 templates each), upgradable to 3000 users.



#### MorphoAccess<sup>®</sup> J-Dual

to be used either for one-tomany identification or one-toone authentication, by combining fingerprint biometrics with MIFARE\*/DESFire\* contactless smartcard technologies.

